

NEW REGISTON PRODUCT BROCHURE

SANDWHEEL C80

Features and Applications

- Safe use even high rotational speed with specially reinforced mesh.
- The structure on its surface eliminates clogging and assures efficient work.
- This wheel is able to process curve also.
- Ideal for cutting plastic such as FRP.



Package



Specifications

Diameter (mm)	Thickness (mm)	Bore (mm)	Grain	Grit	Packing Outer Box (pcs × inner box)	Maximum operation speed
105	2	16	C	80	300pcs (30pcs × 10boxes)	80m/s (4,800m/min)

Product examples

- Always use backup pad.

- Removing the burrs from the FRP boat hull after molding.

When cutting FRP, if clogging occurs on the grinding wheel, the sharpness decreases and the FRP starts to melt. Therefore, it's recommended to use a mesh type wheel that allows for easy dissipation of grinding heat. The SANDWHEEL C80 is a depressed center wheel where the tightening nut is concealed, while the straight wheel is SANDWHEEL C60.



This photo is for illustrative purposes..



This photo is for illustrative purposes..



NEW REGISTON

2-1-1 AYUMINO IZUMI-CITY OSAKA 594-1157 JAPAN

Visit our website
<https://www.newregiston.co.jp/en/>

